

M4006

Super Standalone NVR

GVD M4006 -


full-featured turnkey NVR provides superior recording and display performance from megapixel. Equipped with embedded DOM system, it provides reliability and stability beyond other competitive NVR products. It is the best solution for mid-sized installations, including police offices, factory, government buildings and hypermarkets.

- Super standalone up to 6 HDDs with dual monitor support
- High recording/display performance for
- Best for medium and multi-site applications

Key Feature

- Pre-built 16, 24, 32, 48 channel licenses with up to 6 HDDs for flexible video recording
- Supports large data throughput for multiple megapixel cameras to achieve high local display performance with dual monitor support
- Optional high performance RAID card supports embedded exclusive Time Sector Engine for best video read-write performance on HDDs
- Equips with the robust DOM-based virus resistant Windows embedded platform
- Supports free GVD CMS Client, Remote Client (Web Viewer) and App Client to meet all needs of easy remote monitoring

System Diagram



Camera Support List































































PROBE





Storage Capability

Model	Channel	Compression	Resolution	FPS	7	10	15	30
M4006	32	H.264	2.0M	Day	33	25	17	9
	32	H.264	3.0M		21	16	11	6
	48	H.264	1.3M		29	21	15	8
	48	H.264	2.0M		22	16	11	6




Vertical Market

Mid-size to Large Scale Installation: Police Office, Multi-site Retail Business, Banking, Hotel


M4 Super Standalone NVR

Super NVR Standalone with Dual Monitors Support

Front Panel Layout



Rear Panel Layout



Hardware Specification

Model	M4006				
Processor	Intel® Core™ i5-2400 Processor				
Memory	DDR3-1333 4G				
Operation System	Windows 7 Embedded				
HDD Tray	6				
HDD Max Capacity	4 TB				
RAID Support	RAID 0,1,5,6 (Optional)				
Prebuilt License	16, 24, 32, 48				
Megapixel Recording	D1. 1.3M~20M				
Display Port	2				
Display Mode	64 camera layout				
LAN Port	Gigabit x 2				
USB Port	Front x 4 , Rear x 4				
Dimensions (DxWxH) mm	470 x 430 x 90				
Weight	10 Kg				
Power Supply	400W				
Voltage	100-240VAC(50~60Hz)				
Remote Access	VMS/ CMS/ CMS Client/ Remote Client/ App Client				
	WALL OF ALL THE ALL TH				

*All specifications are subject to change without notic

